

AN ILLUMINATING CHOICE FOR ANY APPLICATION



Agenda

- Introduce Raytec
- Program
- Registration
- Acceptance of Registration
- Product overview
- Support
- Questions

Designed &
Manufactured in the

UK

24/7 Support
Live Chat
Stock in NY Warehouse

Raytec

- Global Leaders in Lighting for Security and Safety
 - Security Division
 - Hazardous Area Division
 - Committed to the Rep model in the Americas for both divisions.

Program

- Eligible Vigitron Manufacturers Representatives (No Competing Lines)
- Register a project with Raytec
- Review the project and accept or reject the registration
- Raytec will provide the design, parts list and quote.
- Once shipped the Vigitron Rep will receive the 3% commission

Program

- Example 1
 - Identify a need in a project with one of your customers
 - Call me directly to discuss the details
 - New Project, no visibility on our end.
 - Design process
 - Sales Channel discussions (Distribution, Integrator and Reps)
 - Quotation provided by Raytec
 - Eligible – Fill out Project Registration
 - Once shipped, finders fee paid to Vigitron Rep (usually 45 days max)
 - Tech support provided by Raytec

Program

- Example 2
 - Identify a need in a project with one of your customers
 - Call me directly to discuss the details
 - Existing Raytec Project or ongoing project
 - Established Raytec Customer
 - Not Eligible

Program



Raytec Project Registration

Raytec Customer

Name:	
Address 1:	
Address 2:	
City:	State/Prov:
Zip/Postal Code:	Country:
Phone:	Email:
Company Contact:	

End User Client

End User Company:	
Address 1:	
Address 2:	
City:	State/Prov:
Zip/Postal Code:	Country:
Phone:	Email:
Project Engineer:	

Integrator/ Dealer Information (if sold through Distribution)

Company Name:	
Address 1:	
Address 2:	
City:	State/Prov:
Zip/Postal Code:	Country:

Project Details

Project Name:	
Scope of Project (# illuminators, model numbers etc.):	
Start Date (approx.):	End Date (approx.):
Raytec Project Value:	
Integrator/Dealer has agreed to register the project with Raytec only: yes <input type="checkbox"/> no <input type="checkbox"/>	
A representative has met with End User: yes <input type="checkbox"/> no <input type="checkbox"/>	
If yes, meeting date:	
Raytec Representative met with:	
If desired, please add any additional remarks or comments:	

Raytec Systems Inc.
800-300 Terry Fox Drive, Kanata Ontario K2K 0E3
T 613 270 9990 F 613 599 5006
alex.tran@rayteccctv.com
www.rayteccctv.com



Program

- New program for Raytec
- Cannot disrupt or confuse our established sales channel
- Will continue to evolve

Product Overview

White-Light



Infra-Red



White-Light adds extra detail including colour of hair, skin tone, colour of vehicle, colour of clothing, patterns/logos.

IR (850nm or 940nm) is strictly monochromatic and articles of clothing and surfaces reflect based on materials and not colour.

IR goes approximately 40% further than the same sized white light illuminator
MUST have a day/night camera with an IR cut filter in order to use IR

White Light



Why use external illuminators?

↓ Watch Bit rate



Why use external illuminators?



4k camera with VARIO i8 (IR) ~900' distance



When details on scene matter

Why use external illuminators?



Video analytics needs lighting to avoid false alarms

The trouble with built in IR...

Built in IR creates a spotlight effect at longer distances



Illuminators provide even illumination across the whole scene



The trouble with built in IR...



Panoramic Lighting



Example of Panoramic Ultra's highly compressed 5° vertical beam pattern

Panoramic Lighting



Complete VARIO2 product line up:



- IR from 250' to 1,650'
- WL from 200' to 820'
- Low Voltage (12/24V AC/DC), power sold separately
- Remote Control Setup
- HRT (Hotspot Reduction Technology)
- Built-in Diagnostics
- 5 year warranty / 10 year lifespan (50, 000 running hours)

Network or PoE Models

- VAR2-IPPoe-i4-1 or i6-1 or i8-1 or i16-1
- VAR2-IPPoe-i4-2 or i6-2 or i8-2
- VAR2-IPPoe-i4-3 or i6-3 or i8-3
- VAR2-POE- i2-1 or i4-1 or i6-1 or i8-1
- VAR2-POE- i2-1 or i4-2 or i6-2 or i8-2
- VAR2-POE- i2-1 or i4-3 or i6-3 or i8-3
- VAR2-IPPoe- w4-1 or w8-1 or w16-1
- VAR2-IPPoe- w4-2 or w8-2
- VAR2-IPPoe-w4-3 or w8-3
- VAR2-POE- w2 or w4-1 or w8-1
- VAR2-POE- w2-2 or w4-2 or w8-2
- VAR2-POE- w3-2 or w4-3 or w8-3
- VAR2- IPPoE-hy4-1 or hy6-1 or hy8-1

Multi-panel Vario2

Double and triple panels available in IR & WL
Allows longer distances OR wider fields of view





Part Codes	Description	Angles	Narrow Angle Distances	Wide Angle Distances
VAR2-i8-2	VARIO2 i8-2 Adaptive Illumination double panel, standard pack 10°x10°, 35°x10° and 60°x25° angles included, 12-24V AC/DC, black, 850nm	10 x 10°	500m (1640ft) at 10°	354m (1161ft) at 20°
		35 x 10° (fitted as standard on all panels)	240m (787ft) at 35°	170m (558ft) at 70°
		60 x 25°	135m (443ft) at 60°	95m (312ft) at 120°
		80 x 30° (optional)	100m (328ft) at 80°	76m (249ft) at 140°
		120 x 50° (optional)	65m (213ft) at 120°	53m (174ft) at 180°

VARIO2 Hybrid

- IR & WL in one panel
- Double stacked LEDs
- IR – 850nm & 940nm option
- WL – coloured LEDs
- Programmable – e.g. IR on photocell/ white light on alarm, timer options for white light duration
- Available in 4, 6, 8 & 16 sized panels



Direct lighting response to camera events...



- Subject appearing in the distance can trigger IR switch to WL
- Loitering triggers a SOS deterrent mode from white light
- Subject approaches fence line, boost WL to 110% for 10s

VARIO 2

EXTREME

Industrial & challenging environments

Extreme:

- Salinity
- Humidity
- Vibration
- Impact Resistance



VARIO2

PULSESTAR

- Pulsestar illuminators deliver powerful pulsed lighting for traffic and machine vision applications
- Pulsed illumination ensures the highest levels of light on scene to illuminate fast moving objects while extending LED life and maximising energy savings
- A **built-in pulse controller** allows the timing, height and width, and the lighting pulse to be tailored for the exact needs of the application, and includes an Ethernet-based communication interface making installation, operation, and maintenance safer and easier.



PULSESTAR i24



VARIO2 PoE

- 4 product sizes
- 8W, 15W, 25W (PoE+) and 49W (PoE++)
- All the features of standard VARIO2
- Plug and play into existing infrastructure
- PoE powered only without communication



VARIO iP

Network Controlled Illuminators



Only 1 CAT5 Available?


- Connects two IP/PoE devices to a PoE switch using a single Cat5/6 cable
- Provides up to 37w to each of 2 devices
- No power source required



NetMux™ Ethernet and PoE Port Multiplexer



Raytec and Vigitron




Desktop Design App



<http://www.raytecdesign.com/users/login>

Free Lighting Design Service



3D Renderings with Photorealistic Lighting Plan

Training



- Monthly webinars on lighting
- Bespoke training available via webinar
- Local manufactures Reps all over NA for on site training and demos
- Presentations at most major security shows

Demo program

- Demo loaner units available
- All reps have a demo loaner kit with WL & IR





Thank you!